

CourtWrap is a laminated Polyester / Vinyl film with a revolutionary, proprietary, long-term repositionable / removable adhesive. CourtWrap is especially designed for indoor sporting hall floors, but can also be used on other smooth, flat surfaces, such as painted metal, glass, tile, sealed concrete, sealed wood, etc...

Extremely easy to install and remove. Repositionable, Dimensionally Stable & Durable. No adhesive residue. You can even wash dust and dirt off the adhesive and reapply the graphic.

## APPLICATIONS

- Indoor Athletic Court Floors (Basketball & Volleyball courts, etc...)
- When used with CourtWrap Protect, textured non-slip laminate. (ASTM D-2047 & R10 certified)
- Temporary vehicle, window or door graphics (no laminate required)

## ADVANTAGES

- Easy Application and Removal
- No Adhesive Residue
- Excellent durability
- Great Heat Resistance and Dimensional Stability
- Cleanable Adhesive
- Universal Printability: UV-Curable, Solvent, Eco-Solvent & Latex Inks

## ADVICE

- For temporary storage, save the original liner and reapply it.
- Dirt & Dust can be cleaned off the adhesive with cold water.
- Rounding Corners helps prevent edge lift.



## MATERIAL

### CourtWrap

- 150 microns (8mil) Polyester (PET) / Vinyl
- Proprietary, long-term Repositionable / Removable Adhesive
- Printable White Front
- Silver metallic back
- 135gsm Siliconized Paper Liner

### CourtWrap Protect

- 120 micron (4.7mil) Textured Vinyl Laminate
- Permanent, Clear, Acrylic Adhesive
- 63gsm Siliconized Paper Liner
- ASTM D-2047 & R10 certified

## PRINTING METHOD

- Solvent, Eco-Solvent
- UV Curable
- Latex
- Screen

## HUMIDITY AND SOLVENT RESISTANCE

very good

## MIN. APPLICATION TEMPERATURE

+10°C to +30°C (+50°F to +86°F)

## SERVICE RANGE TEMPERATURE

-17°C to +50°C (+0°F to +122°F)

## SHELF LIFE

12 months, stored at +20 (68° F) and 50% R.H.

## DURABILITY

- Indoor Floor Applications: 6-12 months
- Indoor Wall & Window Applications: 24-36 months
- Outdoor Window, Wall, Car Applications: 6-12 months
- Clean Removal with No Adhesive Residue

\*for critical substrates, please test prior to application

[www.cgxusa.com](http://www.cgxusa.com)

[info@cgxusa.com](mailto:info@cgxusa.com)

## APPLICATION

- Inks should be fully off-gassed before CourtWrap Protect laminate application.
- Surface must be dry, clean and above 10°C (50°F).

## WARRANTY

Continental Grafix products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the Technical Specification Sheets. Continental Grafix will replace or refund the price of any Continental Grafix materials found not to meet our product specifications. In no case shall Continental Grafix be liable for any direct, indirect, or consequential damages, including labor or non-Continental Grafix materials charges. \*\*The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy of suitability for specific applications.

