

panoRama **Walk&Wall**[®]



Certified for
HP Latex Inks

Textured Non-Slip Vinyl With Repositionable
Adhesive For Indoor/Outdoor Floor And Wall
Graphics

APPLICATIONS

- Tradeshows (Concrete, Carpet & Walls)
- POP (Floor & Wall Graphics)
- Sidewalk Directional Graphics

WWW.CGXUSA.COM

CONTINENTAL
GRAFIX

panoRama Walk&Wall®



MATERIAL

Face Film	White Textured Polymeric PVC
Backing	Dimensionally Stable Fabric Backing
Adhesive	Repositionable Solvent Acrylic
Liner	Polyethylene Coated Liner - 130g/m ²
Thickness	8 mil (200 microns)
FR Certification	ASTM E84, ASTM E648, ASTM E662, B1 & M1
Slip Rating	ASTM D2047, ASTM C1028-07 & R12



DURABILITY

Interior	Floor - Up To 3 Months Wall - Up To 3 Years
Exterior	Sidewalk - Up To 3 Months Wall - Up To 2 Years
Environment	Humidity & Solvent Resistance - Good Resistant To Mild Acids, Alkalis & Salt Solutions
Shelf Life	12 Months
Storage Requirements	Store at +59°F to +68°F (+15°C to +20°C) with a Relative Humidity of 45% to 65%
Repositionable	Yes - On Initial Installation

APPLICATION/REMOVAL

Application Temp	+25°F to +86°F (+10°C to +30°C)
Service Temp	+0°F to +122°F (-17°C to +50°C)
Removability	Cleanly Removable With No Adhesive Residue, Up To 6 Months - Adhesion May Increase Over Time
Removal Temp	+50°F (+10°C) Or Greater
Exclusions	NOT To Be Applied On Fresh Paint, Marble Or Granite Floors (No Exhaustive List Available)

Surface must be clean and dry. Prevent contact with solvent or ammonia based cleaners. For best results, clean surface with a mild detergent and water and dry thoroughly. Always clean and dry surface prior to application.



PRINTING METHODS

Digital - Solvent, Eco-Solvent, Latex & UV Inks



MATERIAL SIZES

48" x 82' & 48" x 164'



ADVANTAGES

- Premium Calendered Vinyl Offers Short To Medium Term Durability At An Affordable Cost
- Great Dimensional Stability
- Universal Paper Liner Enables Easy Handling During Application
- Ease Of Removal With No Adhesive Residue For Up To 6 Months

For additional product information, performance, and warranty guidelines please contact **Continental Grafix USA, Inc.** at 1.704.872.2216 or visit www.cgxusa.com.

Note: For critical substrates, always test prior to application.

WWW.CGXUSA.COM

CONTINENTAL
GRAFIX