



FatFloor

Clear textured printable PVC designed for medium- to long-term floor and wall applications. Provides affordable, enduring protection for wall and floor graphics in high-traffic areas.

Safe for almost any surface, FatFloor has no adhesive, making it a versatile material choice for a wide variety of applications.

Communicate a vibrant, impactful impression in one step with a durable, long-lasting finish.

APPLICATIONS

- Retail Entrances
- Museum Exhibits
- High-Traffic Event Graphics
- Showroom
- Counter Mats

FatFloor

MATERIAL

| | |
|------------------|--------------------------------|
| Face Film | Textured, Transparent PVC Film |
| Back Side | Clear |
| Adhesive | None |
| Liner | None |
| Film Thickness | 55 mil (1400µ +/-10µ) |
| FR Certification | ASTM E84 |
| Slip Resistance | ANSI A137.1/A326.3, R10 |

DURABILITY

| | |
|----------------------|--|
| Exterior | Up to 3 Years Dependent Upon Mechanical Use of the Surface to Which Applied |
| Environment | Humidity & Solvent Resistance – Very Good |
| Shelf Life | 1 Year |
| Storage Requirements | Store at 59°F to 75°F (+ 15°C to +24°C) and Relative Humidity Between 50 and 55% |
| Repositionable | Yes |

APPLICATION/REMOVAL

| | |
|------------------|---------------------------------|
| Application Temp | Minimum +50°F (+10°C)** |
| Service Temp | +0°F to +122°F (-17°C to +50°C) |
| Removal Temp | +50°F (+10°C) or Greater |
| Exclusions | Not Suitable for Polished Stone |

CHEMICAL RESISTANCE

| | | |
|----------------------------|--|--|
| Non-continuous Immersion | <ul style="list-style-type: none">• Water• Bleach• 1% Sodium Hydroxide• Gasoline unleaded | <ul style="list-style-type: none">• 50% Anti-freeze in Water• Mineral Spirits• Isopropyl Alcohol |
| Intermittent Exposure Only | <ul style="list-style-type: none">• 25% Sulphuric Acid | |
| These Are Not Recommended | <ul style="list-style-type: none">• Trichloroethylene | |

**Reverse print on the smooth side of FatFloor and flood with white ink or back with self-wound white material. Color and lot variances of coated surfaces including paints, power coatings, lacquers, stains, and other treatments may vary the performance, and should be evaluated for compatibility prior to use.*

For critical substrates and all surfaces, please test PRIOR to application.

Remarks: The specifications presented above are the average data summarized by PRECEDE under the latest test results. The tolerance has shown to be +/- 5%.



Printing Methods

- Digital - Solvent, Eco-Solvent, UV, & Latex*

**Latex printable on XXL machines only.*



Material Sizes

- 54" x 50'



Advantages

- No Adhesive - Simple Application and Removal. Use Clear Carpet Tape When Tack Is Desired
- Very Robust Construction - Withstands Pedestrian and Auto Traffic
- Slip-Resistant and Chemical-Resistant for Medium- to Long-Term Exterior Use



For more information

For additional product information, performance, and warranty guidelines please contact Continental Gratrix USA, Inc.

704-872-2216 • www.cgxusa.com