

panoRama™



Premium Self-Adhesive Outside Mount
One-Way Vision Film - Available in 80/20,
70/30, 60/40 & 50/50 Film/Hole Patterns

APPLICATIONS

- Retail Windows & Building Wraps
- Vehicle Windows (Rear & Side)
- Exterior Applications Up To 3 Years

WWW.CGXUSA.COM

CONTINENTAL
GRAFIX

panoRama™

MATERIAL

Face Film	Printable White Perforated Polymeric PVC
Backing	Black For Maximum Contrast
Adhesive	Removable Semi-Permanent Solvent Acrylic
Liner	Universal Paper Liner - 4mil
Thickness	6mil (145 microns)
FR Certification	ASTM E84, B1 & M1
Hole Diameter	1.5mm

DURABILITY

Interior	Up To 5 Years
Exterior	Up To 3 Years - Vert. Exposure Under Norm. Cond.
Environment	Humidity & Solvent Resistance - Good
Shelf Life	12 Months
Storage Requirements	Store at +59°F to +68°F (+15°C to +20°C) with a Relative Humidity of 45% to 65%
Repositionable	No

APPLICATION/REMOVAL

Application Temp	+50°F to +86°F (+10°C to +30°C)
Service Temp	+0°F to +122°F (-17°C to +50°C)
Removability	Cleanly Removable With No Adhesive Residue, Up To 6 Months - Adhesion May Increase Over Time
Removal Temp	+50°F (+10°C) Or Greater
Exclusions	NOT To Be Applied On Fresh Paint, Polycarbonate, And Some PVC (No Exhaustive List Available)

Surface must be clean and dry. Prevent contact with solvent or ammonia based cleaners. For best results, clean surface with a mild detergent and water and dry thoroughly. Always clean and dry surface prior to application.



PRINTING METHODS

Digital - Solvent, Eco-Solvent, Latex & UV Inks; Screen Printing; Offset



MATERIAL SIZES See Pricelist For Details

60" x 1312', 54" x 1312', 60" x 100'
54" x 100', 30" x 100', 54" x 30'
30" x 30'



ADVANTAGES

- Premium Material Provides Long Term Durability Of At Least 3 Years
- Available with 4 Film/Hole Patterns
panoRama1520™ 80% Film/20% Hole
panoRama1530™ 70% Film/30% Hole
panoRama1540™ 60% Film/40% Hole
panoRama1550™ 50% Film/50% Hole

For additional product information, performance, and warranty guidelines please contact **Continental Grafix USA, Inc.** at 1.704.872.2216 or visit www.cgxusa.com.

Note: For critical substrates, always test prior to application.

WWW.CGXUSA.COM

CONTINENTAL
GRAFIX