

panoRama Clear™



**Clear Inside Mount Self-Adhesive One Way Vision Film With Full Face Adhesive
80/20 & 70/30 Film/Hole Patterns**

APPLICATIONS

- Retail Windows & Building Wraps
- Vehicle Windows (Rear & Side)
- Interior Applications Up To 2 Years

WWW.CGXUSA.COM

CONTINENTAL
GRAFIX

panoRama Clear™

MATERIAL

Face Film	Clear Gloss Perforated PVC
Backing	Clear
Adhesive	Removable Semi-Permanent Solvent Acrylic
Liner	Polyester Liner - 165g/m ²
Thickness	8mil (205 microns)
FR Certification	Not Tested
Hole Diameter	1.5mm

DURABILITY

Interior	Up To 2 Years - Vert. Exposure Under Norm. Cond.
Exterior	Not Recommended
Environment	Humidity & Solvent Resistance - Good
Shelf Life	12 Months
Storage Requirements	Store at +59°F to +68°F (+15°C to +20°C) with a Relative Humidity of 45% to 65%
Repositionable	No

APPLICATION/REMOVAL

Application Temp	+50°F to +86°F (+10°C to +30°C)
Service Temp	+0°F to +122°F (-17°C to +50°C)
Removability	Cleanly Removable With No Adhesive Residue, Up To 6 Months - Adhesion May Increase Over Time
Removal Temp	+50°F (+10°C) Or Greater
Exclusions	NOT To Be Applied On Fresh Paint, Polycarbonate, And Some PVC (No Exhaustive List Available)

Surface must be clean and dry. Prevent contact with solvent or ammonia based cleaners. For best results, clean surface with a mild detergent and water and dry thoroughly. Always clean and dry surface prior to application.



PRINTING METHODS

Digital - Solvent, Eco-Solvent, Latex & UV Inks; Screen Printing



MATERIAL SIZES

54" x 1312', 54" x 100'



ADVANTAGES

- No Lamination Required On Inside Mount - Window Protects Graphic
- Easy Install On Inside Avoiding Inclement Weather Conditions
- Available with 2 Film/Hole Patterns
Clear8020™ 80% Film/20% Hole
Clear7030™ 70% Film/30% Hole

For additional product information, performance, and warranty guidelines please contact **Continental Grafix USA, Inc.** at 1.704.872.2216 or visit www.cgxusa.com.

Note: For critical substrates, always test prior to application.