

panoRama Film™



PVC Free - Non-Adhesive Inside Mount
One Way Vision Film, Available In
80/20 & 70/30 Film/Hole Patterns

APPLICATIONS

- Retail Windows w/*panoRama Tape™*
- Ceiling Hung Graphics/Room Dividers
- Interior Applications Up To 3 Years

WWW.CGXUSA.COM

CONTINENTAL
GRAFIX

panoRama Film™

MATERIAL

Face Film	Printable White Perforated Polyester Film
Backing	Black For Maximum Contrast
Adhesive	None
Liner	Removable w/Polyester Back - 2mil (50 micron)
Thickness	5.9mil (150 microns)
FR Certification	Not Tested
Hole Diameter	1.5mm

DURABILITY

Interior	Up To 3 Years - Vert. Exposure Under Norm. Cond.
Exterior	Not Recommended
Environment	Humidity & Solvent Resistance - Good
Shelf Life	12 Months
Storage Requirements	Store at +59°F to +77°F (+15°C to +25°C) with a Relative Humidity of 20% to 70%
Repositionable	No

APPLICATION/REMOVAL

Application Temp	+50°F to +86°F (+10°C to +30°C)
Service Temp	+41°F to +104°F (+5°C to +40°C)
Removability	Cleanly Removable With No Adhesive Residue, Up To 6 Months - Adhesion May Increase Over Time
Removal Temp	+50°F (+10°C) Or Greater
Exclusions	NOT To Be Applied On Fresh Paint, Polycarbonate, And Some PVC (No Exhaustive List Available)

Surface must be clean and dry. Prevent contact with solvent or ammonia based cleaners. For best results, clean surface with a mild detergent and water and dry thoroughly. Always clean and dry surface prior to application.



PRINTING METHODS

Digital - Solvent, Eco-Solvent, Latex & UV Inks; Screen Printing



MATERIAL SIZES See Pricelist For Details

60" x 1000', 54" x 1000', 60" x 100'
54" x 100', 54" x 30'



ADVANTAGES

- No Lamination Required On Inside Mount - Window Protects Graphic
- Easy Install On Inside Avoiding Inclement Weather Conditions
- PVC Free Material
- Available with 2 Film/Hole Patterns
Film8020™ 80% Film/20% Hole
Film7030™ 70% Film/30% Hole

For additional product information, performance, and warranty guidelines please contact **Continental Grafix USA, Inc.** at 1.704.872.2216 or visit www.cgxusa.com.

Note: For critical substrates, always test prior to application.

panoRama Tape™

MATERIAL

Face Film	Optically Clear Polyester
Adhesive Inside	Permanent Clear Acrylic - 1mil (25 micron)
Adhesive Outside	Semi-Permanent Clear Acrylic - .75mil (19 micron)
Liner	Removable Polyester - 2mil (51 micron) +/- 10%
Thickness	4mil (102 microns)
FR Certification	Not Tested
Material Size	1" x 200' on a 3" core

DURABILITY

Interior	Up To 1 Year
Exterior	Not Recommended
Environment	Humidity & Solvent Resistance - Good
Shelf Life	12 Months
Storage Requirements	Store at +59°F to +68°F (+15°C to +20°C) with a Relative Humidity of 45% to 65%
Repositionable	Yes

APPLICATION/REMOVAL

Application Temp	+50°F to +86°F (+10°C to +30°C)
Service Temp	+0°F to +122°F (-17°C to +50°C)
Removability	Cleanly Removable With No Adhesive Residue, Up To 6 Months - Adhesion May Increase Over Time
Removal Temp	+50°F (+10°C) Or Greater
Exclusions	NOT To Be Applied On Fresh Paint, Polycarbonate, And Some PVC (No Exhaustive List Available)

Surface must be clean and dry. Prevent contact with solvent or ammonia based cleaners. For best results, clean surface with a mild detergent and water and dry thoroughly. Always clean and dry surface prior to application.



PRINTING METHODS

N/A



MATERIAL SIZES

1" x 200'



ADVANTAGES

- Window Graphics Stay Safely On The Inside For Less Vandalism
- Easy Install On Inside Avoiding Inclement Weather Conditions
- Designed To Work With *panoRama Film8020™* & *panoRama Film7030™*

For additional product information, performance, and warranty guidelines please contact **Continental Grafix USA, Inc.** at 1.704.872.2216 or visit www.cgxusa.com.

Note: For critical substrates, always test prior to application.